

**TMF 55 A**

Cropper mono front head to feed semi-automatic blade, to large cutting capacity. Tilt with electronic control head with three quick buttons -45° 90° $+45^{\circ}$; the interior and exterior angles up to 20° with electronic positioning. Full guarding of work zone with pneumatic control. worktop ground steel. Feed motion of guides and recirculating ball bearings. Movement of blade rotation with pair of tapered bearings. Horizontal pneumatic clamps with low pressure device. feed speed hydropneumatic adjustment. two-hand device of contemporaneity for blade advancement. digital display head tilt display LED. removable drawer chips. Provision for fume extraction nozzle. Pneumatic blade mist lubrication (emulsified oil).

Technical datas

Power supplies treephase	380/400 - 50/60	Volt-Hz
Power motor treephase	2.2	kW
Speed rotating	2850	r.p.m.
Diameter blade	550	mm
Tilt adjustable blade	-20...+20	°
Weight (model 55-55E)	500	kg

Standard equipement

Service spanners
 Use and maintenance manual and ce marking
 Blade with carbide teeth HM Ø550 mm (installed)
 Adjustable leveling feets (installed)
 Air gun for cleaning (installed)

Options

Vertical pneumatic vise
 Tool lubrication pneumatic pulse (neat oil)
 Loading roller: RIS 22-44-66
 Unloading roller: RIS 20M-40M-17V-40V-60V-40E-60E
 Industrial vacuum wheeled model ASP 15