Wadkin Bursgreen AUTHORISED STOCKISTS

A. L. DALTON LTD

CROSSGATE DRIVE
QUEENS DRIVE IND. ESTATE
NOTTINGHAM NG2 1LW
TELEPHONE: 0602 861445



- Safe
- High Output
- Reliable



Accurate



## The Fence

The fence made of ground metal for maximum life is very easily adjusted and has a micro setting for speedy accurate set-ups. Guards and dust chute are provided as standard. (Extraction removed for clarity).




## The Worktable

The large worktable with ground surface and four quickly removable rings supports timber over the full range of cutter sizes (up to 340 mm) ensuring a good finish on all jobs, large or small.




Speed changes and lubrication Speed changes are simple and quick, a single lever slackening or tensioning the belt. Lubrication points are very accessible being grouped together on a small panel for speed and convenience.



Deep Rail Moulding



\*Moulding Curved Surfaces




\*Tenoning



\*Stair Housing



\*Dovetailing



Corner Locking

\*2 Wing Solid Profile Cutters Inexpensive and can be quickly changed. Can be supplied to the profiles shown.

Clearly Marked Controls Fitted to the front panel convenience and ease of operation. The spindle look and brake are operated by foot pedals enabling the operator to use both hands when changing cutters. Both the brake and pindle lock are electrically interlocked to the starter for maximum safety.



No. 8 2 in

tonguing cutter



No. 9 3 in grooving cutter





No. 19 5 in radius ovolo

No. 24 1 in

diameter nosing cutter

No. 42 45

angle cutter







No. 31 1 in



No. 43 30 angle cutter



No. 2 11 in square edge cutter



rsible glue utte



diamete





No. 51 Table

35mm Optional diameters of top 30mm 900×1100mm

Spindle rise and fall Table Height Four circular table plates giving openings of

plates Output of motor

ification liameter of top piece

Table size

Spindle speeds

Speed of motor, 50Hz Speed of motor, 60Hz Floor space Approximate net weight Approximate gross weight Approximate shipping dimensions


or 1½in 36×43in 3000, 4500, 6000, and 8000 rev/min or 3000, 4500, 6000, and 10000 rev/min 150mm 33¾in 855mm

80, 150, 190, 260  $3\frac{1}{4}$ , 6,  $7\frac{1}{2}$ ,  $10\frac{1}{4}$ , 13½in×2in deep 340 × 50mm deep and 355×10mm deep and 14in × €in deep 150×400mm 6×16in 5.5kW 7½hp (7.5kW optional) (10hp optional) 3000 rev/min 3000 rev/min 3600 rev/min 3600 rev/min 900×1100mm 36×43in 890lb 405kg 980lb 445kg

1,00m3

35ft3

\*Optional extras



SALES

## WADKIN LTD.

Green Lane Works, Leicester LE5 4PF, England Telephone: 0533 769111 Telex: 34646 (Wadkin G) Telegrams & Cables: Woodworker, Leicester, Telex

Also York House, Empire Way, Wembley, Middx. HA9 0PA Telephone: 01-902 7714 (3 lines) Telex: 262210

## SERVICE



BURSGREEN (DURHAM) LTD. Fence Houses, Houghton-le-Spring, Tyne and Wear DH4 5RQ.

Telephone: (038 579) 2385. Telex: 53441 As our policy is constantly to improve the design of Bursgreen woodworking machinery, the details given

in this leaflet are not to be regarded as binding.