## Woodworkers' Tool Grinder (BZG)



Wadkin BURSGREEN



# Woodworkers' Tool Grinder







GRINDING

STROPPING


Faster, easier and better woodwork comes naturally when cutting tools are kept properly sharpened. This grinding machine with its fast and slow running spindles, and its combination of coarse grinding wheels, fine oilstone and stropping wheel make it easy for practically every cutting tool used by carpenters, joiners, cabinet makers, pattern makers to be kept sharp.

It is a matter of a few moments only to take

a tool to this grinder and bring it away correctly hollow ground, honed and stropped. The internal oiling system used for the fine oilstone keeps it always ready for use and free from dust or grit.

Every woodworking shop needs this versatile tool grinder. It provides efficient low cost tool maintenance and many years of all round usefulness, the value of which is out of all proportion to its cost.

All tools are securely held to give the correct cutting angle and hollow grind.




GENERAL PURPOSE GRINDING

 $8^{\prime\prime} \times 4^{\prime\prime}$  grinding wheel running at 2000 r.p.m.

5½" × 2" leather coursed stropping wheel running at 2000 r.p.m.

3" × 5" long grinding cone with rest for gouges.

Covers have been removed in this illustration to show the various wheels more clearly.



### Woodworkers' Tool Grinder (BZG)

#### CONSTRUCTION

MAIN FRAME is of robust steel plate construction. It forms a rigid support for the grinding wheel spindles, and completely encloses the drive. Access is through a side panel. The machine embodies slow and fast running spindles. Both spindles run on ball bearings.

DRIVE is from motor hinge mounted inside the main frame. Drive to the fast spindle is by belt direct from the motor. Slow spindle

is driven by belt through intermediate reduction gear. Gear is totally enclosed and runs in oil.

MOTOR is totally enclosed fan cooled and controlled from flush mounted, built in push button stations, one on each side machine. Automatic contactor gear embodies full protective features including no volt and overload releases.

GUARDS. All wheels are provided with detachable guards.



TOOL REST for the slow spindle is adjustable by screw motion to present the cutting tool the correct angle and to apply the feed to the wheek It carries a sliding clamp for the tool which is moved backwards and forwards across the face of the wheel. The tool rest covers the full length of the spindle and permits the clamp being used over either wheel. Tool est for the fast spindle is fully adjustable and designed for flat or angular grinding. A rest is also provided for the grinding cone.

#### CIFICATION

Size of oilstone tup wheel		203mm. × 51mm.
Size of coarse emery cup	8" × 2"	203mm. × 51mm.
Size of emery wheel	04	203mm. × 19mm.
Size of cone Size of stropping wheel	3" × 5"	76mm. × 127mm.
Speed of fast spindle	54 × X	133mm. × 51mm. 2000 r.p.m.

****	300 r.p.m.	
	1 h.p.	960 r.p.m.
4516	2'7" × 2'10"	787 × 864 mm.
1000	41 cwt.	229 kilos.
1550	6½ cwt.	330 kilos.
	23 cu. ft.	.651 cub. met.
	BZEDG.	
	***	1 h.p. 2'7" × 2'10" 4½ cwt. 6½ cwt. 23 cu. ft.

#### DETAILS INCLUDED IN THE PRICE

One cup wheel. Motor and control gear. One fine grain oilstone. One leather stropping wheel. One emery wheel, One cone for sharpening gouges. Two tool rest. Set of spanners. Lubricating pump and tin of lubricant.

SALES & SERVICE

Telegrams: Woodworker-Phone-Leicester Telephones: Leicester 67114 (4 lines) 66021 (3 lines) London Office:

Brookfield House, 62-64, Brook Street, W.1

Telephones: MAYfair 7048 & 9.

Vadkin Itd.

Green Lane Works, Leicester

BURSGREEN machines are manufactured by: BURSGREEN (DURHAM) LTD., Fence Houses Houghton-le-Spring, Co. Durham,

BURSGREEN (COLNE) LTD., Lodge Holme Trawden, Nr Colne Lancs.

Printed in England