

# T500

### **THICKNESSER**



## Perfect finish over complete timber length.

- Low cost. Big capacity.
- Infinitely variable feed speeds.
- Power rise and fall\*
- Increased feeding power.
- 10mm stock removal in one pass.
- Safe Fully guarded. No-volt release and overload protection fitted as standard.
- Easily maintained greased for life bearings.
- Anti-kickback fingers fitted as standard.



#### **Grouped Controls**

For less operator fatigue and ease of operation, controls are grouped conveniently to hand.



#### \*Power Rise and Fall

Rise and fall switch with fine adjustment. And digital read-out for ease of operation and repeatable accuracy.



#### Stock Control With Safety

Sectional chipbreaker over the whole width of material. And anti-kickback fingers fitted as standard.



#### **\*Sectional Feed Rolls** High productivity with multiple feeding of timber of uneven thickness.



#### \*Built In Grinder

A further aid to productivity. Cutters can be ground without removing them from the machine - saving "down-time". Encourages regular sharpening of knives.

\*Optional extra

#### Specification

Capacity of machine Feed speed H.P. of Cutterblock mote Speed of Cutterbloo Speed of motor Speed of motor **6**0 Hz Dia. of cutting circle Dia. of feed rollers Minimum stock length Maximum stock removal H.P. of rise and fall motor \*

Length of table Floor space Net weight approx. Gross weight approx. Shipping dimensions



button.



(20-60 ft/min)

(7½ hp)

00 rpm (43/4 in) (31/4 in) 85 mm 280 mm (11 in) 10 mm (% in) 0.25 kW (1/3 hp) 1000 mm (39 in) 1000 x 1030 mm (39 x 40 in) 580 kg (1278 lb) 700 kg (1543 lb) 1.64 m<sup>3</sup> (58 ft<sup>3</sup>)

High Quality, Robust and Effortless to Operate



Wadkin Durham, Fence Houses, Houghton-le-Spring, Tyne & Wear, DH4 5RQ, England. Telephone: (091) 385 2385. Telex: 53441 (Burdrm G). Fax: (091) 385 3311

As our policy is constantly to improve the design, details given in this leaflet are not to be regarded as binding.