

Wadkin  
Bursgreen

**BER 2 75**

## Medium Duty Spindle Moulder



**Note:**

UK machines must have Shaw Guard fitted, see back page.

- **Soundly Engineered**  
Vibration free running for accurate work
- **High Quality Finish**  
Reduces sanding time-saves money
- **Versatile**  
Will take a wide variety of cutter equipment
- **Safe**  
Fully guarded. No volt overload release fitted as standard



**The Fence**

The steel fence is easily adjusted by rack and pinion and hand levers. The guard is fully adjustable for maximum safety. Guard and dust chute are fitted as standard. (Extraction removed for clarity).



**The Worktable**

The generously proportioned worktable, 915 x 760mm (36 x 30in) with precision ground surface and two quickly removable rings, supports timber over the full range of cutter sizes, up to 170mm (6 7/8 in) ensuring a good finish on a wide range of timber sections large or small.




**Speed Changes**

Speed changes are simple and quick. A conveniently placed handwheel slackens or tensions the belt. The flat belt drive ensures efficient power transmission and is quiet and reliable.



### Control Box

Four controls incorporated into one box for easy and safe operation



### \*Tenoning Attachment

With this useful attachment tenons up to 50mm (2in) long can be worked.



### \*Dovetailing

As both male and female dovetail are produced at the same time a good fit is assured.




### \*Shaping.

A large variety of shaped work can be produced using slotted collars as shown, or using circular or profile cutterblocks with ring fences (Universal guard removed for clarity).



### \*Shaw Guard

Shaw type guard providing top and side pressure being used with standard fence and guard.



### \*Wadkin Bursgreen BLG8 Autofeed

Easily fitted. Greatly increases output, maintains consistency of finish, reduces operator fatigue and increases safety.

### \*2 Wing Solid Profile Cutters

Inexpensive and can be quickly changed. Can be supplied to the profiles shown.



No. 2 1 1/2 in square edge cutter



No. 8 3/8 in tonguing cutter



No. 9 3/8 in grooving cutter



No. 13 Reversible glue joint cutter



No. 19 3/8 in radius ovolo cutter



No. 22 3/4 in diameter nosing cutter



No. 23 1/2 in diameter nosing cutter



No. 24 1 in diameter nosing cutter



No. 36 3/8 in radius ogee cutter



No. 42 45° angle cutter



No. 43 30° angle cutter

### \*Optional Extras

### Specification

Diameter of top piece

Size of table

Speed of spindle

Rise and fall of spindle

Table height

Two circular table plates

giving openings of

Size of fence plates

Power of motor, (3 phase)

Power of motor, (Single phase)

Speed of motor, 50 Hz

Floor space

Approximate net weight

Approximate gross weight

Approximate shipping dimensions

30mm	or	1 1/4 in
760 x 915mm		30 x 36 in
4,500 and 7000 rev/min		
75mm		3 in
850mm		33 1/2 in

170, 90, 70mm	6 5/8, 3 1/2, 2 3/4 in
355 x 115mm	14 x 4 1/2 in

2.2kW	3hp
3kW (optional)	4hp (optional)
2.2kW (optional)	3hp (optional)
3000 rev/min	3000 rev/min
760 x 915mm	30 x 36 in
230kg	510 lb
320kg	710 lb
0.87m <sup>3</sup>	30.8 ft <sup>3</sup>

### SALES

#### WADKIN PLC

Green Lane Works, Leicester LE5 4PF, England  
Telephone: 0533 769111 Telex: 34646 (Wadkin G)  
Telegrams & Cables: Woodworker, Leicester, Telex

### SERVICE

#### BURSGREEN (COLNE)

Lodge Holme, Trawden, Nr Colne, Lancs.  
Telephone: (0282) 865310, Telex: 635032

As our policy is constantly to improve the design of Bursgreen woodworking machinery, the details given in this leaflet are not to be regarded as binding

