



TMA 42 - TMA 42A

Single head sawing machine with manual or semi-automatic feed knife in "SA" version, with large cutting capacity thanks to the adjustable vertical. Tilt head with three fixed positions -45° 90° $+45^\circ$. worktop ground steel, upward movement of the head and vertical support rails and recirculating ball grantisce rigidity and precision. The vertical pneumatic clamps with low pressure device and integral work area protection impose the machine at the highest safety levels. feed speed hydropneumatic adjustment (version SA). Removable swarf collecting drawer and preparation for attack aspotazione fumes make the car clean and tidy. Pneumatic blade mist lubrication (emulsified oil).

Technical datas

Power supplies treephase	380/400 - 50/60	Volt-Hz
Power motor treephase	3100	kW
Speed rotating blade	1.5	r.p.m.
Diameter blade	420	mm
Vertical fence adjustable	0...-100	mm
Tilt adjustable blade	-15...+15	°
Weight (model 42-42A)	230	kg

Standard equipment

Service spanners
 Use and maintenance manual and ce marking
 Blade with carbide teeth HM Ø420 mm (installed)
 2 Tunnel accident prevention side L = 800 mm
 Attack suction mouth Ø70 mm
 Adjustable leveling feets (installed)
 Air gun for cleaning (installed)

Options

Horizontal vice pneumatic
 Loading roller: RIS 22-44-66
 Unloading roller: RIS 20M-40M-17V-40V-60V-40E-60E
 Industrial vacuum wheeled model ASP 15