



## TMA 60A

Single head sawing machine with large cutting capacity to feed semi-automatic blade. adjustable vertical fence in two positions to increase the cutting capacity; cutting angle up to 15° right and left with three fixed positions -45°, 0°, +45° for quick placement. Integral cutting area protection with lateral tunnel accident prevention. Work ground steel, upward movement up head on guides and recirculating grantisce rigidity and precision ball over time. The vertical pneumatic clamps with low pressure device and integral work area protection impose the machine at the highest safety levels. feed speed hydropneumatic adjustment. Removable swarf collecting drawer and preparation for attack aspotazione fumes make the car clean and tidy. Pneumatic blade mist lubrication (emulsified oil).

## Technical datas

Power supplies treephase	380/400 - 50/60	Volt-Hz
Power motor treephase	5.5	kW
Speed rotating blade	2850	r.p.m.
Diameter blade	600	mm
2 Positions vertical fence	0/180	mm
Tilt adjustable blade	-15...+15	°
Weight	500	kg

## Standard equipment

Service spanners  
 Use and maintenance manual and ce marking  
 Blade with carbide teeth HM Ø600 mm (installed)  
 2 Side antinfortunistici tunnel L = 500 mm  
 Adjustable leveling feet (installed)  
 Air gun for cleaning (installed)

## Options

Tool lubrication pulse (neat oil)  
 Shavings drawer pull  
 Loading roller: RIS 22-44-66  
 Unloading roller: RIS 20M-40M-17V-40V-60V-40E-60E  
 Industrial vacuum wheeled model ASP 15  
 Electronic blade tilt display  
 Carter apertuta / closing pneumatic